


Końcówki kablowe

Końcówki rurkowe, izolowane nylonem, seria standardowa

- Materiał: Miedź elektrolityczna 99,9%
- Powierzchnia: cynowane • z wżernikiem
- Izolacja: czarne



Cu

Art. nr.	p.prz.	M	d1	d2	d4	a	l	ciężar/100 sztuk	sztuk
29 08 00	10	5	7	5,5	9	17	35,5	0,500	100
29 08 01		6		6,5			35,5	0,500	100
29 08 02		8		8,5			42	0,600	100
29 08 04		10		10,5			46	0,700	100
29 08 06	16	5	8,5	5,5	10,5	21	39,5	0,900	100
29 08 10		6		6,5			41,3	0,900	100
29 08 12		8		8,5			45,5	1,000	100
29 08 14		10		10,5			49,5	1,100	100
29 08 16		12		13,0			54	1,100	100
29 08 18	25	6	10	6,5	12	24	46,5	1,300	100
29 08 20		8		8,5			51	1,400	100
29 08 22		10		10,5			55	1,600	100
29 08 24		12		13,0			57	1,500	100
29 08 26	35	6	12	6,5	14,5	27	49,5	2,000	100
29 08 30		8		8,5			54	2,200	100
29 08 32		10		10,5			59	2,300	100
29 08 34		12		13,0			61	2,300	100
29 08 36	50	6	14	6,5	16,5	32	59	3,200	100
29 08 40		8		8,5			59	3,200	100
29 08 42		10		10,5			63	3,300	100
29 08 44		12		13,0			68	3,500	100
29 08 46		14		15,0			71,5	3,500	100
29 08 48	70	8	16,4	8,5	18,9	33,5	65,5	4,700	100
29 08 50		10		10,5			66,5	4,800	50
29 08 52		12		13,0			70,5	4,900	50
29 08 54		14		15,0			73,5	5,000	50
29 08 56		16		17,0			78,5	4,500	50
29 08 58	95	8	17,8	8,5	20,8	40	74	5,900	50
29 08 60		10		10,5			74	5,800	25
29 08 62		12		13,0			76	6,000	25
29 08 64		14		15,0			79,5	6,000	25
29 08 66		16		17,0			84	6,200	25
29 08 68	120	8	19,3	8,5	22,3	41,5	80,5	7,200	25
29 08 70		10		10,5			80,5	7,000	25
29 08 72		12		13,0			80,5	6,800	25
29 08 74		14		15,0			82,5	6,900	25
29 08 76		16		17,0			85,5	7,000	25
29 08 78	150	10	20,8	10,5	23,8	48	88	8,200	25
29 08 80		12		13,0			89	8,300	25
29 08 82		14		15,0			90	8,200	25
29 08 84		16		17,0			92	8,100	25
29 08 86		20		21,0			106	9,400	25

1
2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32

haupa®

...rozwiązania, które przekonują