


Kątowe końcówki kablowe

Kątowe końcówki kablowe 90° DIN 46235

- **Materiał:** Miedź elektrolityczna 99,9%
- **Wymiary rurek według DIN 46235**
- **Powierzchnia:** cynowane




Cu

Art. nr.	p.prz.	Zacisk sześciokątny				d1	d2	d4	a	b	c1	c2	ciężar/100	sztuk
		M	KZ	wąskie	szersokie									
29 17 00	6	5	5	2		3,8	5,3	5,5	10	8,5	6,5	9,0	0,300	100
29 17 02		6		2			6,4			8,5	7,5	10,0	0,300	100
29 17 04	10	5	6	2		4,5	5,3	6	10	9,0	7,0	10,0	0,340	100
29 17 06		6		2			6,4			9,0	7,5	10,0	0,350	100
29 17 08		8		2			8,4			13,0	10,0	13,0	0,370	100
29 17 10	16	6	8	2	1	5,5	6,4	8,5	20	13,0	7,5	11,0	1,200	100
29 17 12		8		2	1		8,4			13,0	10,0	13,0	1,300	100
29 17 14		10		2	1		10,5			17,0	12,0	15,0	1,400	100
29 17 16		12		2	1		13,0			18,0	13,0	18,0	1,300	100
29 17 18	25	6	10	2	1	7	6,4	10	20	14,0	7,5	11,0	1,500	100
29 17 20		8		2	1		8,4			16,0	10,0	13,0	1,600	100
29 17 22		10		2	1		10,5			17,0	12,0	15,0	1,600	100
29 17 24		12		2	1		13,0			19,0	13,0	18,0	1,700	100
29 17 26	35	8		2	1	8,2	8,4	12,5	20	17,0	10,0	13,0	2,700	100
29 17 28		10		2	1		10,5			19,0	12,0	15,0	2,800	100
29 17 30		12		2	1		13,0			21,0	13,0	18,0	2,800	100
29 17 32	50	8	14	3	1	10	8,4	14,5	28	20,0	10,0	16,0	4,400	100
29 17 34		10		3	1		10,5			22,0	12,0	16,0	4,500	100
29 17 36		12		3	1		13,0			24,0	13,0	18,0	4,500	100
29 17 38		16		3	1		17,0			28,0	16,0	22,0	4,600	100
29 17 40	70	8	16	3	1	11,5	8,4	16,5	28	24,0	10,0	14,0	6,000	100
29 17 42		10		3	1		10,5			24,0	12,0	16,0	6,300	100
29 17 44		12		3	1		13,0			24,0	13,0	18,0	6,300	100
29 17 46		16		3	1		17,0			30,0	16,0	22,0	6,600	100
29 17 48	95	10	18	4	2	13,5	10,5	19	35	28,0	12,0	17,0	9,000	50
29 17 50		12		4	2		13,0			28,0	13,0	18,0	9,300	50
29 17 52		16		4	2		17,0			32,0	16,0	22,0	9,000	50
29 17 54	120	10	20	4	2	15,5	10,5	21	35	32,0	15,0	17,0	10,400	50
29 17 56		12		4	2		13,0			32,0	16,0	18,0	10,700	50
29 17 58		16		4	2		17,0			32,0	18,0	22,0	10,700	50
29 17 60		20		4	2		21,0			38,0	21,0	24,0	11,000	50
29 17 62	150	10	22	4	2	17	10,5	23,5	35	34,0	15,0	17,0	14,200	50
29 17 64		12		4	2		13,0			34,0	16,0	18,0	14,300	50
29 17 66		16		4	2		17,0			34,0	19,0	22,0	15,200	50
29 17 68		20		4	2		21,0			40,0	21,0	24,0	15,700	50
29 17 70	185	10	25	4	2	19	10,5	25,5	40	37,0	15,0	22,0	18,600	50
29 17 72		12		4	2		13,0			37,0	16,0	22,0	18,700	50
29 17 74		16		4	2		17,0			37,0	19,0	22,0	19,000	50
29 17 76		20		4	2		21,0			40,0	21,0	24,0	18,700	50
29 17 78	240	12	28	5	2	21,5	13,0	29	40	42,0	16,0	22,0	25,100	50
29 17 80		16		5	2		17,0			42,0	19,0	22,0	25,000	50
29 17 82		20		5	2		21,0			45,0	21,0	24,0	25,300	50

Kątowe końcówki kablowe 45° DIN 46235

- **Materiał:** Miedź elektrolityczna 99,9%
- **Wymiary rurek według DIN 46235**
- **Powierzchnia:** cynowane



Cu

Art. nr.	p.prz.	Zacisk sześciokątny				d1	d2	d4	a	b	c1	c2	ciężar/10	sztuk
		M	KZ	wąskie	szerokie									
29 18 00	6	5	5	2		3,8	5,5	5,5	10	8,5	6,5	9,0	0,300	100
29 18 02		6		2			6,4			8,5	7,5	10,0	0,300	100
29 18 04	10	5	6	2		4,5	5,3	6	10	9,0	7,0	10,0	0,400	100
29 18 06		6		2			6,4			9,0	7,5	10,0	0,350	100
29 18 08		8		2			8,4			13,0	10,0	13,0	0,400	100
29 18 10	16	6	8	2	1	5,5	6,4	8,5	20	13,0	7,5	11,0	1,200	100
29 18 12		8		2	1		8,4			13,0	10,0	13,0	1,300	100
29 18 14		10		2	1		10,5			17,0	12,0	15,0	1,400	100
29 18 16		12		2	1		13,0			18,0	13,0	18,0	1,300	100
29 18 18	25	6	10	2	1	7	6,4	10	20	14,0	7,5	11,0	1,500	100
29 18 20		8		2	1		8,4			16,0	10,0	13,0	1,600	100
29 18 22		10		2	1		10,5			17,0	12,0	15,0	1,600	100
29 18 24		12		2	1		13,0			19,0	13,0	18,0	1,700	100
29 18 26	35	8		2	1	8,2	8,4	12,5	20	17,0	10,0	13,0	2,700	100
29 18 28		10		2	1		10,5			19,0	12,0	15,0	2,800	100
29 18 30		12		2	1		13,0			21,0	13,0	18,0	2,800	100
29 18 32	50	8	14	3	1	10	8,4	14,5	28	20,0	10,0	16,0	4,400	100
29 18 34		10		3	1		10,5			22,0	12,0	16,0	4,500	100
29 18 36		12		3	1		13,0			24,0	13,0	18,0	4,500	100
29 18 38		16		3	1		17,0			28,0	16,0	22,0	4,600	100
29 18 40	70	8	16	3	1	11,5	8,4	16,5	28	24,0	10,0	14,0	6,000	100
29 18 42		10		3	1		10,5			24,0	12,0	16,0	6,300	100
29 18 44		12		3	1		13,0			24,0	13,0	18,0	6,300	100
29 18 46		16		3	1		17,0			30,0	16,0	22,0	6,600	100
29 18 48	95	10	18	4	2	13,5	10,5	19	35	28,0	12,0	17,0	9,000	50
29 18 50		12		4	2		13,0			28,0	13,0	18,0	9,300	50
29 18 52		16		4	2		17,0			32,0	16,0	22,0	9,000	50
29 18 54	120	10	20	4	2	15,5	10,5	21	35	32,0	15,0	17,0	10,400	50
29 18 56		12		4	2		13,0			32,0	16,0	18,0	10,700	50
29 18 58		16		4	2		17,0			32,0	18,0	22,0	10,700	50
29 18 60		20		4	2		21,0			38,0	21,0	24,0	11,000	50
29 18 62	150	10	22	4	2	17	10,5	23,5	35	34,0	15,0	17,0	14,200	50
29 18 64		12		4	2		13,0			34,0	16,0	18,0	14,300	50
29 18 66		16		4	2		17,0			34,0	19,0	22,0	15,200	50
29 18 68		20		4	2		21,0			40,0	21,0	24,0	15,700	50
29 18 70	185	10	25	4	2	19	10,5	25,5	40	37,0	15,0	22,0	18,600	50
29 18 72		12		4	2		13,0			37,0	16,0	22,0	18,700	50
29 18 74		16		4	2		17,0			37,0	19,0	22,0	19,000	50
29 18 76		20		4	2		21,0			40,0	21,0	24,0	18,700	50
29 18 78	240	12	28	5	2	21,5	13,0	29	40	42,0	16,0	22,0	25,100	50
29 18 80		16		5	2		17,0			42,0	19,0	22,0	25,000	50
29 18 82		20		5	2		21,0			45,0	21,0	24,0	25,300	50

haupa®

...rozwiązania, które przekonują